

**POST-DEPOSITION ANNEALED RECORDING MEDIA AND METHOD OF
MANUFACTURING THE SAME**

Related Applications and Publications

5 This application claims priority from Provisional Application Serial No.
60/182,427 filed February 14, 2000, entitled "METHOD TO MANUFACTURE
RECORDING MEDIA USING POST-DEPOSITION ANNEALING," the entire
disclosure of which is hereby incorporated herein by reference. The inventors prior
publication entitled "Recording Performance Enhancement via in-situ Annealing of
10 Multilayer Media Structures," published January 11, 2001, at the 8th Joint MMM-
Intermag Conference, is hereby incorporated herein by reference.

Field of Invention

15 This invention relates to magnetic recording media, such as thin film magnetic
recording disks, and to a method of manufacturing the media. The invention has
particular applicability to high areal density magnetic recording media exhibiting low
noise, and high coercivity.

Background of the Invention

20 The increasing demands for higher areal recording density impose increasingly
greater demands on thin film magnetic recording media in terms of remanent coercivity
(Hr), magnetic remanance (Mr), coercivity squareness (S*), medium noise, i.e., signal-to-
medium noise ratio (SMNR), and narrow track recording performance. It is extremely

difficult to produce a magnetic recording medium satisfying such demanding requirements.

The linear recording density can be increased by increasing the Hr of the magnetic recording medium, and by decreasing the medium noise, as by maintaining very fine magnetically non-coupled grains. Medium noise in thin films is a dominant factor restricting increased recording density of high-density magnetic hard disk drives, and is attributed primarily to inhomogeneous grain size and intergranular exchange coupling. Accordingly, in order to increase linear density, medium noise must be minimized by suitable microstructure control.

10 It is recognized that the magnetic properties, such as Hr, Mr, S* and SMNR, which are critical to the performance of a magnetic alloy film, depend primarily upon the microstructure of the magnetic layer which, in turn, is influenced by the underlying layers, such as the underlayer. It is also recognized that underlayers having a fine grain structure are highly desirable, particular for growing fine grains of hexagonal close
15 packed (HCP) Co-alloys deposited thereon.

Previous attempts to improve the SMNR and coercive force with increasing areal density have used *ex situ* post-deposition annealing of the magnetic thin film to reduce anisotropy without increasing grain size. Such attempts have met with limited success in providing a suitable product with increased coercivity, however, due to the introduction
20 of environmental contaminants and the need to expose the thin film to high temperatures over a relatively long period of time to achieve satisfactory results. The annealing conditions employed have subjected the thin film to oxygen and, thereby, required the use of thick caplayers. The thick caplayers of the prior art result in unacceptable head-to-

media spacing that can interfere with the operation of devices employing this type of recording media such as hard disk drives.

In U.S. Patent No. 5,989,728 to Coffey et al., an *ex situ* post-deposition annealing process is described in which a CoPt thin film of 25 nm to 200 nm is annealed at 550°C to 750°C for approximately 10 minutes. Coffey states that it is preferable, however, to anneal the thin film at 650°C to 700°C. Further, the annealing process of Coffey requires the use of a quartz lamp furnace with flowing Ar/4%H₂ gas to prevent oxidation.

In U.S. Patent No. 6,117,282 to Kuo et al., a method for producing a Magnetic recording medium thin film is described wherein the CoTb magnetic layer is protected by a SiNx layer having a thickness of approximately 10 nm and annealed at 250°C for approximately 60 minutes in a vacuum furnace. Kuo et al. do not describe the signal characteristics or SMNR of their described recording media. The major disadvantages of the Kuo process are the following. First, annealing is performed in a vacuum furnace, which is *ex situ* from the sputtering chamber in which the SiNx layer was deposited. When annealing is performed *ex situ*, it is intractable to prevent oxygen from entering the magnetic layer, thus deteriorating the performance of the recording media. Second, the large energy requirement to maintain the annealing temperature for a long period of time, greatly increasing the cost of the recording medium.

It would therefore be desirable to have a magnetic recording medium with a minimal Cr content that exhibits high coercivity and a high signal to medium noise ratio.

It would also be advantageous to have a method of producing a recording medium that provides a magnetic recording medium with a high linear recording density, high signal to noise ratio, and high coercivity that can be integrated into current manufacturing

processes economically and efficiently where the recording medium does not need to be exposed to high energy sources for long periods of time or removed or subjected to multiple manufacturing process such as the *ex situ* annealing process of Coffey.

In short, there exists a need for a process of manufacturing a magnetic recording medium in accordance with the criteria stated above that does not achieve increased coercivity through grain coarsening or increasing Cr content.

Summary of the Invention

One embodiment of this invention is a magnetic recording medium, comprising a substrate, a magnetic recording layer and a caplayer, wherein the caplayer has been annealed *in situ*. "*In situ*" annealing means that the medium was annealed during the manufacturing process without having to remove the medium from a sputtering system to a separate location. Preferably, the *in situ* annealing is at a temperature of from about 150°C to about 550°C for a period of from about 10 seconds to about one minute.

The caplayer could comprise CrMn and have a thickness of from about 0.5 nm to about 5 nm, and wherein less than about 15 at.% of the caplayer is Cr. The medium could have M_r/H_c less than about 50 or 20 nm. The medium could have SMNR of about 5 dB greater than that of another medium except wherein the caplayer is not annealed. The medium could SMNR of about 12 dB or more. The medium could have M_r of less than about 0.6 memu/cm² and an H_c of greater than about 2000 or 3000 kOe.

Another embodiment of this invention is a method of manufacturing a magnetic recording medium, comprising depositing a magnetic recording layer on a substrate, depositing a caplayer on the magnetic recording layer and annealing the caplayer *in situ*

at a temperature of from about 150°C to about 550°C. The method could further comprise depositing a layer comprising CoCrPt on the substrate prior to depositing the caplayer. The method could further comprise depositing a protective layer on the caplayer after annealing. The annealing could be carried out at from about 250°C to
5 about 350°C. The annealing could be carried out for less than about 30 seconds. In a preferred embodiment, the annealing is carried out for about 14 seconds at a temperature of about 300°C.

Another embodiment of the process could further comprise depositing a sub-seed layer on the substrate; depositing a seed layer on the substrate; depositing an underlayer
10 on the seed layer and depositing a intermediate layer on the underlayer; wherein the magnetic layer is deposited on the intermediate layer.

The magnetic layer could comprise at least one of Co, Cr, B, Pt, Ta, and Nb. The magnetic layer could comprise a layer of CoCrPt having a thickness of from about 100 nm to about 400 nm.

15 Another embodiment is a magnetic recording medium, comprising a magnetic recording layer and means for low noise recording. The means for low noise recording includes an annealed layer on the magnetic layer and equivalents thereof. Preferably, the annealed layer comprises CrMn and has been annealed *in situ*.

Additional advantages and other features of the present invention will be set forth
20 in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from the practice of the present invention. The advantages of the present invention may be realized and obtained as particularly pointed out in the appended claims. As will be

realized, the present invention is capable of other and different embodiments, and its several details are capable of modifications in various obvious respects, all without departing from the present invention. The drawings and description are to be regarded as illustrative in nature, and not as restrictive.

5

Brief Description of the Drawings

Figure 1. A schematic representation of a process to produce flyable recording media having been processed with post-deposition annealing.

10 Figure 2(a). An illustration of Hcr vs. Mrt for as-deposited and as-annealed samples.

Figure 2(b). Further illustration of Hcr vs. Mrt for as deposited and as-annealed samples.

15 Figure 2(c). A graphical representation of the SMNR vs. Mrt/Hcr for as-deposited and as-annealed samples.

Figure 2(d). A graphical representation of signal strength vs. Mrt for as-
20 deposited and as-annealed samples.

Figure 3. Grain size analysis from plan view dark field TEM showing that for the annealed samples there is no grain coarsening or change in granular morphology observed within statistical confidence.

5 Figure 4. Plan view TEM micrograph showing distinct and wide grain boundaries typical of CoCrPtB magnetic alloys.

Figure 5. CoPtTaB Hcr and Mrt normalization curves for various annealing temperatures as a function of annealing duration (normalized to room temperature
10 values).

Figure 6. Plan view of a bright field TEM micrographs of as-deposited and annealed at 550°C for 115 sec CrMn/CoCrPtTaB/Cr/NiAl samples showing significant grain coarsening from extreme thermal treatment.

15 The invention will be better understood by reference to the Detailed Description of the Invention when taken together with the attached drawings.

Detailed Description of the Invention

20 It has been found that a magnetic recording film having high coercivity can be produced without increasing the grain size of the magnetic layer while maintaining the Cr content below about 15 at.% (atomic percent). Through a novel application of the process of post-deposition annealing, recording media employing larger magnetic alloys

can be produced with very high linear recording densities and high signal-to-medium-noise ratio (SMNR).

According to one embodiment of the invention, the recording media of the present invention has a caplayer ranging in thickness of from about 0.5 nm to about 5.0 nm deposited on the magnetic layer of the medium by maintaining a system base pressure of 1×10^{-7} Torr with less than 50% partial pressure from background water and then using depositing means such as a disc sputtering system. Preferred is the Intevac MDP-250B system. To obtain a multilayer structure, the depositing means may also include a standard dc-magnetron-sputtering unit.

Using the disc sputtering system in conjunction with a standard DC-Magnetron sputtering unit, a multilayer structure could be applied to a super-polished glass-ceramic substrate beginning with a NiAl-based seedlayer, a Cr-based underlayer, and a CoCrPt magnetic layer. A caplayer is applied on the magnetic layer. The caplayer ranges in thickness from 0.5 to 5 nm.

The caplayer and the caplayer means should have a Cr content of less than about 15 at.% and preferably comprises CrMn. Once the caplayer has been deposited on the magnetic layer, the recording medium is annealed *in situ*. The preferred means for annealing the caplayer is an infrared heater in the range of 10-20 kW installed in the medium processing sequence to permit *in situ* heating of the medium during fabrication.

In a preferred embodiment, a 12 kW infrared heater is used to allow the caplayer to be subjected to 250°C-300°C for a period not to exceed 15 seconds. Preferably the caplayer has a thickness of about 0.8 nm and is annealed for 15 seconds at 300°C.

Prior to the deposition of the caplayer, a magnetic recording medium can be prepared which comprises a substrate means for supporting a magnetic recording film and a magnetic recording means for recording data, wherein the magnetic recording means is located on the substrate means and comprises CoCrPt, CoCrPtB, or CoPtTaB, with CoCrPt being preferred. The substrate means includes any substrate such as a glass, glass-ceramic, NiP/aluminum, metal alloys, plastic/polymer material, ceramic, glass-polymer, composite materials or other non-magnetic materials. The magnetic recording means is a material capable of being magnetized, typically in the form of a magnetic layer.

10 The magnetic recording film comprises a sub-seed layer of a thickness of about 10 Å to about 1000 Å, a seed layer of a thickness of about 10 Å to about 2000 Å, an underlayer of a thickness of about 10 Å to about 1000 Å, an intermediate layer of a thickness of about 1.5 Å to about 150 Å, and a magnetic layer of a thickness of about 100 Å to about 400 Å.

15 In a preferred embodiment, the thickness of the seedlayer is 200 Å to about 1600 Å, preferably between 300 Å and 1200 Å, and most preferably about 600 Å. The thickness of the underlayer is 12 Å to about 500 Å, preferably between 15 Å and 250 Å, and most preferably about 25 Å. The thickness of the magnetic layer is 150 Å to about 250 Å, preferably between 175 Å and 225 Å, and most preferably about 200 Å. The
20 thickness of the protective layer is 20 Å to about 300 Å, preferably between 30 Å and 100 Å, and most preferably about 50 Å. The protective layer is made of hydrogenated carbon (CH_x).

The magnetic recording medium has a remanent coercivity of about 2000 to about 10,000 Oersted, and an Mrt (product of remanance, Mr, and magnetic layer thickness, t) of about 0.2 to about 2.0 memu/cm². In a preferred embodiment, the coercivity is about 2500 to about 9000 Oersted, more preferably in the range of about 3000 to about 6000 Oersted, and most preferably in the range of about 3350 to about 5000 Oersted. In a preferred embodiment, the Mrt is about 0.25 to about 1 memu/cm², more preferably in the range of about 0.3 to about 0.7 memu/cm², and most preferably in the range of about 0.3 to about 0.6 memu/cm².

This invention will be better understood with reference to the following examples, which are intended to illustrate specific embodiments within the overall scope of the invention as claimed.

Examples

Example 1

Media samples were fabricated using an Intevac MDP-250B disc sputtering system (Fig. 1), which in this example was both the means for depositing on a substrate a caplayer and the means for annealing the caplayer. System base pressure (B.P.) was maintained below 1×10^{-7} Torr with < 50% partial pressure from background water. Standard dc-magnetron sputtering units were used in conjunction with the system to apply regular media multilayer structures generally composed of NiAl-based seedlayers, Cr-based underlayers and various magnetic layers to super-polished Ohara glass-ceramic substrates. CoCrPt, CoCrPtB, and CoPtTaB magnetic compositions were selected based on inherently high exchange coupling, wide grain boundary width, and narrow grain

boundary width respectively. Deposition substrate temperature was maintained at 270°C. Crystallite sheet texture for all structure-types fabricated was confirmed to be (112) for the sublayer and (10.0) for corresponding magnetic layers using x-ray diffraction (XRD). In addition to the standard multilayer configuration, a caplayer of CrMn was applied to the top surface of the magnetic layer. A caplayer of CrMn is applied to the magnetic layer with a thickness of 0.8 nm and annealed *in situ* with a 12 kW infrared heater at 300°C for 15 seconds. Additional samples were processed *ex-situ* using a Modular Process Technology RTP-6005 capable of reaching temperatures of 1200 °C.

Recording parametrics were measured using a Guzik 1701MP spinstand tester and magnetic properties were determined from vibrating sample magnetometer (VSM) measurements. Microstructural data was collected from transmission electron microscopy (TEM), and XRD.

Shown in Fig. 2(a) is the coercive force of the as-deposited and as-annealed samples for media having CrMn/CoCrPt/Cr/NiAl multilayer structures, with a caplayer of 0.8 nm of CrMn. The annealed sample was *in-situ* post annealed at 300 °C for 15 seconds. The data show that annealing greatly boosts the coercive force of the as-deposited samples. A peak of 3809 Oe is reached at 0.43 memu/cm² with an s* of 0.82 compared to ~1000 Oe with s* equal to 0.90 for the as-deposited samples. The decrease in s* is indicative of a decrease in intergranular exchange field coupling as the magnetic grains tend more toward Stoner-Wolfarth-like particles. There is also a perceptible shift to lower M_{rt} when samples are annealed. VSM measurements confirm a 16% drop in M_s due to annealing. This is attributed to migration of Mn atoms into the bulk core of the grain from both the grain boundary and the caplayer. Chromium dilution of the core is

disregarded due to the observation that the magnetization was not significantly affected by thermal treatment of CoCrPt films without a caplayer. Since the caplayer thickness, 8 Å is similar to that of the grain boundary, the concentration gradients would be approximately equivalent for Cr into the grain. Therefore, it is reasonable to assume that
5 a pure Cr caplayer would not change the results.

Plotted in Fig. 2(b) is the SMNR vs. M_{rt}/H_{cr} (an analog of the transition parameter) for both sample groups. The corresponding signal and noise of the two sample groups are shown in Fig. 2(c) and Fig. 2(d), respectively. The data show that annealing increases the signal and reduces the noise therefore resulting in higher SMNR.
10 Comparing samples of the same original M_{rt} , the SMNR gain is as large as 10 dB, or 216% improvement. This phenomenon is the result of the diffusion of CrMn from the caplayer to the grain boundary thereby greatly reducing the exchange coupling among grains. This granular decoupling then results in better transition sharpness and therefore more signal and less noise. This is consistent with the model given by Bertram in H.N. Bertram, *Theory of Magnetic Recording*, Cambridge, 1994, p.130, wherein the signal, V
15 $\propto e^{-a}$, where, a , is the transition parameter.

Grain size analysis was performed for the above samples to rule out the possibility of the higher coercive force arising from grain coarsening. In Fig. 3, micrographs for both as-deposited and as-annealed are shown with comparative statistics.
20 It is observed that there is no statistical difference between the two mean grain sizes. Therefore, it is reasonable to conclude that the increase in coercive force due to annealing is a result of the magnetic particles tending more toward single-domain with a coherent rotation mechanism of switching. The data confirms that the annealing process of this

invention does not cause an increase in grain size, unlike previous attempts to use annealing to produce a high coercivity magnetic film with a low Cr content in the magnetic layer which employed higher temperatures and/or longer annealing times.

5 Comparative Example 1

The same post-deposition annealing process of Example 1 was applied to a composition identical in Cr, and Pt level as in the CoCrPt alloy with the addition of a few atomic percent of B as it has been observed that B tends to increase effective grain boundary width. This is shown in the plan-view TEM micrograph in Fig. 4. The grains
10 in this figure are clearly delineated by the amorphous registering region interposed. The width of these boundaries is much greater than was shown in Fig. 3 (or than will be shown in Fig. 6). However, these samples were unresponsive to the usable range of *in-situ* annealing temperatures (200-450°C) in terms of H_{cr}, or SMNR enhancement.

Table 1 shows the performance data of media in which the CoCrPtB layer is as-
15 deposited and as *in-situ* annealed post deposition. The as-annealed samples were exposed to 400°C for 15 seconds.

Table 1: Effect of Post Deposition Annealing on CoCrPtB.

Sample	Mrt memu/cm ²	Hcr Oe	SMNR dB	pw50 μin
As-deposited	0.45	3037	17.2	8.0
As-annealed	0.45	3033	17.3	8.0

Comparative Example 2

A Cr-less alloy, CoPtTaB was also investigated as a viable sample containing relatively small grain boundary width. Again, it was not possible to anneal with any effect on recording properties *in-situ*.

5 Comparative Example 3

Samples were annealed *ex-situ* to determine the threshold for coercive force increase. In Fig. 5 it is observed that above 400 °C annealing temperature and 15 seconds duration time, the coercive force finally begins to increase. The peak occurs for 550 °C and 60 seconds. Commensurate decrease in Mrt for all samples analyzed is slight compared to the large increase in coercive force. It is also observed that for the annealing condition: 550 °C, 115 sec., the coercive force has decreased from the peak value ~11%. In Fig. 6 bright field TEM images show qualitatively, but clearly that for this particular thermal treatment there is grain coarsening occurring.

15 Comparative Example 4

The recording medium of Comparative Example 4 is the same as that of Example 1 except the caplayer was omitted from the structure. It was observed that here was no observable change in the magnetic performance of the recording medium of Comparative Example 4 after the *in-situ post* anneal similar to that of Example 1.

20 The above description is presented to enable a person skilled in the art to make and use the invention, and is provided in the context of a particular application and its requirements. Various modifications to the preferred embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be

applied to other embodiments and applications without departing from the spirit and scope of the invention. Thus, this invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features disclosed herein. The entire disclosure of the patents and publications
5 referred in this application are hereby incorporated herein by reference.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000